Please type a plus sign (+) inside this box

+

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

ttorney Docket No.	003239.P010	Total Pages	41	õ
First Nam	ned Inventor or Application	n Identifier		ρ

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Ziici i cui W	i cuci wang		
ress Mail I ahel No	FI 105035674US		

		•	•				<u> </u>
	LICATION ELEMENTS 600 concerning utility patent application contents	ADI	DRESS TO:	3ox Pa	nt Commissio tent Applicatio Igton, DC 202		jog
1. Submit an 2. Specifica (preferred a - Descrip - Cross F - Statem - Referen	Ismittal Form original, and a duplicate for fee processing) ation [Total Pages 27] arrangement set forth below) otive title of the Invention References to Related Applications ent Regarding Fed sponsored R & D ince to Microfiche Appendix ound of the Invention	<b>.</b>	7. Nucleotide and/or a (if applicable, all n a. Comput	Amino ecess er Rea Copy (	Acid Sequence (ary)  adable Copy  identical to the		
- Brief Si	ummary of the Invention	i	ACCOMPANY	/ING	APPLICA	TION PARTS	
- Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure  3. Drawing(s) (35 CFR 113) [Total Pages 7]  4. Oath or Declaration [Total Pages 2]  a. Newly executed (original copy)  b. Copy from a prior application (37 CFR 1.63(d))  [Note Box 5 below]  [Note Box 5 below]  [Note Box 5 below]  DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application see 37 CFR 1.63(d)(2) and 1.33(b).  5. Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the			Assignment P  37 CFR 3.73(I) (when there is an I) English Transl Information D Statement (ID Preliminary Ar Return Receip (Should be specifi Small Entity Statement(s) Certified Copy (if foreign price)	o) States signeration I isclos S)/PT mendrot Poscally ite.	clement (in Document (in Docume	Copies of IDS Citations P 503)  filed in prior applica proper and desired	6
	e therein.  TNUING APPLICATION, check approp	riate box and supp	olv the requisite information	n:			
_		tinuation-in-part			ation No:		
			CE ADDRESS	-			
Customer	Customer Number of Bar Code Label  (Insert Customer No. or Attach bare code label here)						
NAME	BLAKELY, SOKOLOFF	TAYLOR &	ZAFMAN LLP				
IVAIVIE	-						
	12400 Wilshire Boulevard, Seventh					·	
ADDRESS							
CITY	Los Angeles	STATE	California	ZI	P CODE	90025	
COUNTRY	U.S.A.	TELEPHONE	(714) 557-3800		FAX	(714) 557-334	7

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PTO/SB/17 (10/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE	TR	ΔN	SI	AITT	ΑL

Note: Effective October 1, 1997. Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT

912.00 (\$)

<del></del>	· · · · · · · · · · · · · · · · · · ·		
Complete If Known			
Application Number			
Filing Date	August 14, 1998		
First Named Inventor	Zifei Peter Wang		
Group Art Unit			
Examiner Name			
Attorney Docket Number	003230 P010		

METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)		
The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:	3. ADDITIONAL FEE		
Deposit	Large Entity Small Entity  Fee Fee Fee Fee Fee Description	Fee Paid	
Account Number 02-2666	Code (\$) Code (\$)		
Deposit	105 130 205 65 Surcharge - late filing fee or oath		
Account Name  Blakely, Sokoloff, Taylor & Zafman LLP	127 50 227 25 Surcharge - late provisional filing fee or cover sheet.		
Charge Any Additional Charge the Issue Fee Set in 37	139 130 139 130 Non-English specification		
Charge Any Additional Charge the Issue Fee Set in 37 CFR 1.16 and 1.17 CFR 1.18 at the Mailing of the Notice of Allowance, 37 CFR	147 2,520 147 2,520 For filing a request for reexamination		
1.311(b)  2. X Payment Enclosed:	112 920 112 920 Requesting publication of SIR prior to Examiner action		
Check Money Other	113 1,840 113 1,840 Requesting publication of SIR after Examiner action		
FEE CALCULATION (fees effective 10/01/96)	115 110 215 55 Extension for response within first month		
FEE CALCOLATION (1885 GRECTIVE TO/01/30)	116 400 216 200 Extension for response within second month		
1. FILING FEE	117 950 217 475 Extension for response within third month		
Large Entity Small Entity	118 1,510 218 755 Extension for response within fourth month		
Fee Fee Fee Fee Description Fee Paid	d 119 310 219 155 Notice of Appeal		
Code (\$) Code (\$)	120 310 220 155 Filing a brief in support of an appeal		
101 790 201 395 Utility filing fee \$790	121 270 221 135 Request for oral hearing		
106 330 206 165 Design filing fee	138 1,510 138 1,510 Petition to institute a public use proceeding	ļ	
107 540 207 270 Plant filing fee	140 110 240 55 Petition to revive unavoidably abandoned	}	
108 790 208 395 Reissue filing fee	application	<u> </u>	
114 150 214 75 Provisional filing fee	141 1,320 241 660 Petition to revive unintentionally abandoned application		
SUBTOTAL (1) (\$) 790.00	142 1,320 242 660 Utility issue fee (or reissue)		
2. CLAIMS Extra Fee from Fee Paid	143 450 243 225 Design issue fee		
below below	144 670 244 335 Plant issue fee		
Total Claims 18 -20 = 0 X \$22.00 = 0.00	122 130 122 130 Petitions to the Commissioner	-	
Independent 4 -3 = 1 X \$82.00 = 82.00	0 123 50 123 50 Petitions related to provisional applications		
Multiple Dependent Claims =	126 240 126 240 Submission of Information Disclosure Stmt	ļ	
Large Entity Small Entity	581 40 581 40 Recording each patent assignment per	40.00	
Fee Fee Fee Fee Description	property (times number of properties)	40.00	
Code (\$) Code (\$)	146 790 246 395 Filing a submission after final rejection (37 CFR 1.129(a))		
103 22 203 11 Claims in excess of 20	` '"		
102 82 202 41 Independent claims in excess of 3	149 790 249 395 For each additional invention to be examined (37 CFR 1.129(b))		
104 270 204 135 Multiple Dependent claim	Other fee (specify)		
109 82 209 41 Reissue independent claims over original patent	Other fee (specify)		
110 22 210 11 Reissue claims in excess of 20 and over original patent			
SUBTOTAL (2) (\$) 82.00	O *Reduced by Basic Filing Fee Paid SUBTOTAL (2) (\$)	40.00	

Complete (if applicable) SUBMITTED BY Typed or William W. Schaal, Reg. No. 39, 018 Reg. Number Printed Name Deposit Account Date 02-2666 08/14/98 Signature User ID

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

## APPLICATION FOR UNITED STATES PATENT

#### FOR

# A VOICE ACTIVITY DETECTOR FOR PACKET VOICE NETWORK

Inventor:

ZIFEI PETER WANG

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN 12400 Wilshire Boulevard, Seventh Floor Los Angeles, California 90025-1026 (714) 557-3800

#### **BACKGROUND**

#### 1. Field

5

10

15

20

The present invention relates to the field of data communications. In particular, this invention relates to a system and method for enhancing the reliability of voice activity detection.

### 2. General Background

For many years, discontinuous transmission (DTX) systems have been installed to conserve bandwidth over packet voice/data networks. Bandwidth conservation is accomplished by detecting when a caller is speaking and transmitting speech packets generated by a speech coder during those periods of time. For the remaining periods of time when the caller is not speaking, certain DTX systems have been configured to transmit a background noise level tracked by a voice activating detector. This background noise level is subsequently used to replicate the background silence gaps between communications, which are a considerable portion of normal speech communications.

Conventional DTX systems consist of a voice activity detector (VAD) and a comfort noise generator (CNG). Normally, a "voice activity detector" (VAD) is software processed by circuitry to digitize an analog signal (e.g., voice and/or background noise) and to determine whether or not a particular segment of the digitized analog signal represents a person's voice. Since the range of a person's voice is dynamic, in some situations varying 20-40 decibels (dB), and background noise can vary moment to moment, a number of

003239.P010 -1- WWS/wlr

10

15

20

25

different parameters have been used by conventional VADs to discern voice activity.

For example, an IEEE publication entitled "Application of an LPC" distance measure to the voice-unvoiced-silence detection problem," authored by L.R. Rabiner and M.R. Sambur, describes a voice activity detector (VAD) performing a pattern recognition approach on incoming digitally sampled signals to detect voice activity. In particular, this VAD creates templates of parameters for voiced, unvoiced (e.g., tailing off sounds for certain words) and silence segments of speech. Each template includes five parameters: the energy of the signal (E<sub>s</sub>); the zero-crossing rate of the signal (N<sub>z</sub>); the autocorrelation coefficient at unit sample delay (C1); the first order predictor coefficient (A<sub>1</sub>); and the normalized prediction error (E<sub>p</sub>). Through probability calculations, decision logic compares the templates with a sampled segment of an incoming signal to determine whether the segment represents voice, unvoice or silence. The disadvantage associated with this VAD is that it is extremely difficult to find a set of reliable templates to distinguish between a variety of speech signals and numerous levels of background noise found in different environments.

Another example of VAD involves the use of linear prediction coefficients (LPC) which are calculated in the speech coder. While taking advantage of the LPCs calculated in the speech coders reduce computational power consumption by the VAD, it also has encountered a number of disadvantages. For example, speech coders in accordance with the International Telegraph and Telephone Consultive Committee (CCITT) G.729B standards perform linear predictive coding differently than speech coders in accordance with CCITT G.723 standards. As a result, there does not

003239.P010 -2- WWS/wlr

10

15

20

exist a VAD which can be used by virtually all types of speech coders. Instead, depending on the type of speech coder implemented, the VAD must be modified to operate in combination with that speech coder. This increases overall ownership costs and the difficulty in upgrading the DTX system.

Over the last few years, MICOM Communications Corporation of Simi Valley, California, has produced voice/data networking products for DTX systems that utilize a universal energy-based VAD. The voice/data networking products includes a dual-mode speech coding function in order to achieve bandwidth efficiency. In a VOICE mode, a selected speech coder is responsible for compressing voice signals before transmission and for decompressing the voice signals upon reception. In a SILENCE SUPPRESSION mode, only the background noise level signal is transmitted, from which white noise is regenerated at the destination.

Currently, two parameters are used by this universal VAD function in order to determine whether the voice/data networking product is operating in a VOICE mode or a SILENCE SUPPRESSION mode. These parameters include (i) short-term tracking energy and (ii) long-term tracking energy. The "short-term tracking energy" is an accumulation of signal energy associated with voice signaling and background noise level, and thus, is represented by equation (1).

(1) 
$$E_{trk}(k) = \alpha \times E_{db}(k) + (1-\alpha) \times E_{trk}(k-1),$$
 where  $\alpha = \begin{cases} \frac{1}{4} & \text{if } E_{db}(k) \ge E_{trk}(k-1), \text{ or } \\ \frac{1}{8} & \text{otherwise.} \end{cases}$ 

10

15

20

25

 $E_{dB}(k) \text{ denotes the current frame energy in decibels and is}$  equivalent to the following:  $10 \log_{10} \left( \sum_{n=0}^{n=N-1} s(n)^2 \right) \text{ where "N"}$  represents the number of samples per frame.

 $E_{trk}(k-1)$  denotes the short-term tracking energy for the previous frame.

The "long-term tracking energy" represents the background noise level associated with incoming audio and is measured by equation (2).

(2) 
$$E_l(k) = \min\{\beta E_l(k-1) + (1-\beta)E_s(k), E_{max}\}$$
, where  $\beta$ =0.875; and

E<sub>max</sub> denotes the maximum background level.

As a result, when the calculated value of the long-term tracking energy approaches the calculated value of the short-term tracking energy, the VAD predicts that a segment of sampled signals associated with a current frame is likely to be silence. One problem that has been encountered is that this conventional VAD is subject to increased switching between VOICE mode and SILENCE SUPPRESSION mode during long periods of silence, where the long-term tracking energy naturally approaches the short-term tracking energy. This increasing switching, referred to as "in/out effects," causes audio volume fluctuations detectable by the human ear.

Hence, it would be advantageous to provide a system and method for enhancing reliability of voice activity detection through development of an improved, universal VAD which relies on a peak-to-mean likelihood ratio. The peak-to-mean likelihood ratio reduces the occurrence of the in/out effects by further assisting the VAD, in certain instances, to determine whether an incoming analog signal represents voice or silence.

003239.P010 -4- WWS/wlr

10

15

#### SUMMARY OF THE INVENTION

The present invention relates to a voice activity detector, being either software executable by a processing unit or firmware, which predicts whether an audio frame represents a voice signal or silence. This prediction is based the analysis of a number of parameters, including a short-term averaged energy (STAE), a long-term averaged energy (LTAE), and a peak-to-mean likelihood ratio (PMLR).

In one embodiment, to predict whether a frame represents voice or silence, an initial determination is made whether a sum of the STAE and a factor is greater than the LTAE. If the sum is less than the LTAE, the audio frame represents silence. Otherwise, a second determination is made as to whether the difference between the LTAE and the STAE is less than a predetermined threshold. In the event that the difference between the LTAE and the STAE is less than the predetermined threshold, the PMLR is determined and compared to a selected threshold. If the PMLR is greater than the selected threshold, the audio frame represents a voice signal. Otherwise, it represents silence.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The features and advantages of the present invention will become apparent from the following detailed description of the present invention in which:

Figure 1 is an illustrative diagram of a system comprising a first networking device operating in accordance with the present invention.

Figure 2 is an illustrative diagram of an embodiment of a communication module employed within the first networking device of Figure 1.

Figure 3 is an illustrative flowchart of the operations of the first networking device of Figure 1.

Figure 4 is an illustrative block diagram of the data structure of a service frame.

Figure 5 is an illustrative block diagram of the data structure of a silence suppression frame.

Figure 6 is an illustrative flowchart of the operations of the second networking device.

Figure 7 is an illustrative block diagram of the operations of the comfort noise generator.

20 Figure 8 is an illustrative flowchart of the operations of the voice activating detector.

Figure 9 is an illustrative block diagram of hardware for calculating the average peak-mean ratio.

Figure 10 is an illustrative block diagram of a state diagram of a decision smoothing state machine for further reduction of in/out effects.

10

15

20

#### DETAILED DESCRIPTION OF AN EMBODIMENT

Herein, embodiments of the present invention relates to a system and method for enhancing reliability in voice activity detection. This is accomplished by an improved voice activity detector in which an additional parameter, a peak-to-mean likelihood ratio (PMLR), is used in combination with long-term averaged energy and short-term averaged energy parameters to determine whether various segments of audio constitute voice or silence. The use of the peak-to-mean likelihood ratio by the voice activity detector will reduce audio degradation currently experienced by conventional DTX systems.

Herein, certain terminology is used to describe various features of the present invention. In general, a "system" comprises one or more networking devices coupled together through corresponding signal lines. A "networking device" comprises a digital platform such as, for example, a MARATHON<sup>TM</sup> frame relay product by Nortel/MICOM, a voice-over Asynchronous Transfer Mode (ATM) product such as Passport 4740<sup>TM</sup> by Nortel/MICOM, cellular telephones operating in accordance with a cellular communication standard (e.g., GSM) and the like. Such a digital platform usually comprises software and/or hardware to perform analog to linear conversion, echo cancellation, speed coding, etc.. A "signal line" includes any communications link capable of transmitting digital information at some ascertainable bandwidth.

Examples of a signal line include a variety of mediums such as T1/E1, frame relay, private leased line, satellite, microwave, fiber optic, cable, wireless communications (e.g., radio frequency "RF") or even a logical link.

10

15

20

25

Additionally, "information" generally comprises a signal having one or more bits of data, address, control or any combination thereof. A "communication module" includes a voice activity detector used to determine whether various segments of audio constitute voice or silence. In this embodiment, the "voice activity detector" (VAD) is software; however, it is contemplated that the VAD may be implemented in its entirety as hardware or firmware being a combination of hardware and software.

Referring to Figure 1, an illustrative embodiment of a system utilizing the present invention is shown. Herein, system 100 includes a first networking device (source) 110 coupled to a second networking device (destination) 120 via a signal line 130. Herein, networking device 110 receives analog audio signals 140 as input and digitizes the audio to produce pulse code modulation (PCM) audio for example. The PCM audio is separated into multiple frames, where various signal characteristics of each frame are analyzed by a voice activating detector (VAD) as described below in Figure 8. From these signal characteristics, first networking device 110 can determine whether to transmit a compressed audio frame (referred to as a "service frame") or to transmit a silence suppression frame providing a noise background level as described below.

Referring now to Figure 2, first networking device 110 comprises a communication module 200. Communication module 200 includes a substrate 210 which is formed with any type of material or combination of materials upon which integrated circuit (IC) devices can be attached. Communication module 200 is adapted to a connector 220 in order to exchange information with other logic mounted on a circuit board 260 of networking device 110 for example. Any style for connector 220 may be used,

003239.P010 -9- WWS/wlr

10

15

20

25

including a standard female edge connector, a pin field connector, a socket, a network interface card (NIC) connection and the like.

As shown, communication module 200 includes memory 230 and a processing unit 240. In this embodiment, memory 230 includes off-chip volatile memory to contain software which, when executed by processing unit 240, performs voice activity detection. Of course, non-volatile memory may be used in combination with or in lieu of volatile memory. Processing unit 240 includes, but is not limited or restricted to a general purpose microprocessor, a digital signal processor, a micro-controller or any other logic having software processing capabilities. Processing unit 240 includes on-chip internal memory (M) 250 to receive information from memory 230 for internal storage thereby enhancing its processing speed.

Referring now to Figure 3, an illustrative flowchart of the operations performed by first networking device 110 is shown. Initially, first networking device 110 receives analog audio and digitizes the audio. For this example, the audio may be converted into PCM audio (block 300). The PCM audio is modified by an echo canceler (block 310), in order to eliminate echo returned from second networking device 120 of Figure 1, and thereafter, each frame of the PCM audio is analyzed by a voice activity detector (VAD). For example, the VAD may be software executed by processing unit 240 of Figure 2 (block 320). Based on signal characteristics of each PCM audio frame, a determination is made whether the frame constitutes voice or silence (block 330).

If the frame is determined to be voice, first networking device 110 enters into a VOICE mode. In this mode, the PCM audio frame is loaded into

10

15

20

25

a speech coder which compresses the PCM audio frame to produce a service frame as shown in Figure 4 (block 340). The service frame 260 includes a header 265 to identify the frame and payload 270 to contain compressed audio. Such compression is performed in accordance with any existing or later developed compression function.

Alternatively, if the frame is determined to be silence, first networking device enters into a SILENCE SUPPRESSION mode. In this mode, a silence suppression frame (see Figure 5) is transmitted to the second networking device (block 350). The silence suppression frame 275 comprises a header 280, a first field 285 to contain a background noise level being an energy value representing the background noise, and a second field 290 to contain the complement of the background noise level. The complement is included for error checking. This process, inclusive of voice activity detection, continues for each PCM audio frame (block 360).

Referring now to Figure 6, an illustrative flowchart of the operations performed by second networking device 120 of Figure 1 is shown. Upon receiving a frame of information (block 400), second networking device 120 determines whether a silence suppression frame has been received (block 410). If so, the background noise level recovered from the silence suppression frame is loaded into a comfort noise generator (CNG). The CNG produces comfort noise samples based on the received background level in order to avoid audio artifacts such as in-out effects (block 420).

In particular, as shown in Figure 7, CNG 500 includes linear factor calculator 510 to handle various ranges of background noise levels. Each of these ranges (in dB) is mapped into a linear factor 520 which is used to scale a

003239.P010 -11- WWS/wlr

10

15

20

constant level of noise 530 supplied by a random number generator. The scaled white noise 540 is then passed through a first order 1/f filter 550 to obtain the pink noise samples. The resultant pink noise is a regeneration of the background noise at the source. Thereafter, the pink noise samples are placed in an analog format (block 430) as shown in Figure 6.

Referring still to Figure 6, in the alternative event that a service frame is detected so no error condition is triggered (blocks 440-450), the service frame is transferred to a speech decoder to recover a substantial portion of the original PCM audio (block 460). Thereafter, the PCM audio is placed in an analog format (block 430).

Referring to Figure 8, an illustrative flowchart of the operations of the voice activity detector (VAD) is shown. Initially, each audio frame is collected for N samples per frame (block 600). In this embodiment, the sampling number "N" is approximately 80 samples per frame, but may be any number of samples up to the size supported by a speech coder. After the audio frame has been collected, a number of signal parameters are calculated, including the short-term averaged energy, the long-term averaged energy, and the peak-to-mean likelihood ratio.

Before calculating the short-term averaged energy and the long-term averaged energy, the energy associated with the current audio frame is calculated (block 610). This is accomplished by squaring each voice sample (s<sub>i</sub>) for the current audio frame and summing the squared result. The frame energy is defined by equation (3).

(3) 
$$E = \sum_{i=0}^{N-1} (s_i)^2$$

003239.P010 -12- WWS/wlr

After the current frame energy has been calculated, it is converted into a decibel (dB) value (block 620). This provides a larger dynamic range to handle a greater energy variance for each sampled audio frame. The frame energy (in dB) is calculated as shown in equation (4).

5 (4) 
$$E_{dB} = 10 \log_{10}(E)$$

After calculating  $E_{dB}$  for the current frame, the short term averaged energy may be calculated (block 630). The short-term averaged energy (STAE) is an accumulation of signal energy associated with successive PCM audio frames. The current frame energy  $E_{dB}$  and the STAE for the previous frame are weighted by predetermined factors " $\alpha$ " and "1- $\alpha$ " so that the resultant value is the STAE for the current frame. The selection of the factor " $\alpha$ " may be set through simulations. Herein, the STAE is defined in equation (5) as:

(5) 
$$E_s(k) = \alpha \times E_{dB}(k) + (1-\alpha) \times E_s(k-1)$$
, where 
$$\alpha = \begin{cases} 0.125 \text{ if } E_{dB}(k) \ge E_s(k-1) \\ 0.25 \text{ otherwise.} \end{cases}$$

value.

15

20

10

" $\alpha$ " denotes a selected factor of the energy of a current PCM audio frame to be added to the accumulated average.

"E<sub>dB</sub>(k)" denotes the current frame energy in decibels; and "E<sub>s</sub>(k-1)" denotes the prior short-term averaged energy

Along with the STAE, the "long-term averaged energy" (LTAE) is calculated (block 640). The LTAE is defined as an additional level of accumulation to track the background noise level and, for this embodiment, is updated in accordance with equation (6):

10

15

20

$$(6) \qquad E_{x}(k) = \begin{cases} \min\{\beta E_{x}(k-1) + (1-\beta)E_{s}(k), \; E_{max}\}, \; \text{if } E_{x}(k-1) > E_{s}(k) \\ \min\{E_{x}(k-1) + \delta E_{x}, \; E_{max}\}, \; \text{otherwise} \end{cases}$$

where  $\beta = 0.875$ 

$$\delta E_x = \begin{cases} 1 \text{ if previous form is voice,} \\ \frac{1}{16} \text{ otherwise.} \end{cases}$$

 $E_{\text{max}}$  denotes the maximum background level being set to -30 dBm0.

In the case where  $E_x(k-1) < E_s(k)$ , instead of adaptively updating LTAE, we apply a jump  $(\delta E_x)$ . By doing so, we can update the LTAE promptly when there is a sudden change in background noise level.

Next, a peak-to-mean ratio (PMR) is calculated in order to determine the peak-to-mean likelihood ratio (block 650). The PMR comprises a ratio between the absolute value of a maximum sampled signal and the summation of the values for all (N) sampled signals for the current frame as shown in equation (7). Therefore, as the value of the PMR increases, there is a greater likelihood that the current frame represents silence because a waveform associated with silence has lesser energy than a waveform associated with voice.

(7) 
$$PMR = \frac{\max\{|s_i|\}}{\sum_{i=0}^{N-1}|s_i|}$$

After the PMR is calculated, an average peak-to-mean ratio (APMR) is now determined (block 660) for use in calculating the peak-mean likelihood ratio (PMLR). The reason for calculating APMR is to prevent frequent

003239.P010 -14- WWS/wlr

20

5

alterations between VOICE mode and SILENCE SUPPRESSION mode based on environmental conditions (e.g., speaker talks loudly, noisy environment, etc.). Consequently, the occurrence of an in/out effect is substantially mitigated.

As shown in Figure 9, one technique to calculate the APMR is to implement a circular buffer 700 having depth "M". During analysis by the VAD, the PMR for that frame is inserted into buffer 700. After each insertion, the APMR is calculated by averaging all of the PMRs loaded into buffer 700 based on equation (8):

10 (8) APMR = 
$$\frac{1}{M} \sum_{i=0}^{M-1} PMR_i$$

Referring back to Figure 8, it is contemplated that the PMR and APMR may be used for voice activity detection. The behavior of PMR or APMR may vary, depending on the audible level of the speaker's voice or the background noise. Thus, in this embodiment, a normalized parameter, namely a peakmean likelihood ratio, is calculated and subsequently used to determine whether a sampled frame represents voice or silence (block 670).

More specifically, the peak-mean likelihood ratio (PMLR) is a parameter which is compared with a predetermined threshold value to determine whether a sampled frame represents voice or silence. This threshold value is programmed during simulation, allowing a customer to select an acceptable tradeoff between voice quality and bandwidth savings.

As shown in equation (9) below, the PMLR is normalized to substantially mitigate modification caused by different speakers and different background noise levels. As a result, PMLR has minimal variation between

003239.P010 -15- WWS/wlr

10

15

audio frames in order to discourage in/out effects due to frequent switching between VOICE mode and SILENCE SUPPRESSION mode. Also, PMLR is independent of frame size, and thus, can operate with speech coders supporting different frame sizes.

To determine the PMLR, the VAD keeps track of the maximum APMR (APMR<sub>max</sub>) and the minimum APMR (APMR<sub>min</sub>) contained in buffer 700 of Figure 9. The contents of buffer 700 may be periodically cleared after a selected period of time has expired or after a selected number (S) of calls ( $S\geq 1$ ). From these values and the APMR associated with the current audio frame, the PMLR can be measured by equation (9).

(9) 
$$PMLR_{k} = \frac{\left(APMR_{max} - APMR_{k}\right)}{\left(APMR_{max} - APMR_{min}\right)}$$

In block 680, based on the STAE, LTAE and PMLR parameters, the VAD performs a bifurcated decision process to determine whether a sampled audio frame is voice or silence. A first determination is whether the combination of the STAE and a selected factor is greater than the LTAE as shown in equation (10). The factor is set based on simulation results, which was determined to be 2 dB in this embodiment. Of course, as the factor is increased, more bandwidth will be conserved because there is greater probability for the system to be placed in a VOICE mode.

20 (10) STAE + factor(2dB)
$$\geq$$
LTAE

If the combination is greater than the LTAE, the sampled audio frame is initially considered to be voice. As a result, the VAD performs a second determination. This determination involves ascertaining the PMLR when the LTAE and the STAE differ by less than a predetermined threshold. The

003239.P010 -16- WWS/wlr

10

15

20

predetermined threshold is determined to be 4 dB in this embodiment. In mathematical terms:

| LTAE - STAE | < Threshold (4dB)

When this condition is met, the VAD determines whether the PMLR is less than a selected threshold. The selected threshold is determined to be 0.50 in this embodiment. If the PMLR is less than the selected threshold, the sampled audio frame represents silence. Otherwise, it represents voice. Consequently, the PMLR provides a secondary determination when the LTAE is approaching the STAE to avoid needless in/out effects.

Once the determination has been made that the sampled audio frame is voice or silence, the VAD performs a decision smoothing process (block 690). The decision smoothing function delays the system from switching from the VOICE mode to the SILENCE SUPPRESSION mode immediately after the current frame is detected to be silence. This avoids speech clipping at the end of an utterance.

Referring now to Figure 10, a state diagram concerning the operations of a decision smoothing state machine 800 of the VAD is shown. State machine 800 comprises a VOICE (mode) state 810, a SILENCE SUPPRESSION state 820 and a HANGOVER state 830. For each sampled audio frame, state machine 800 determines the operating state of the system. In the HANGOVER state 830, the system operates as in the VOICE state.

As shown, state machine 800 enters or remains in VOICE state 810 if the current audio frame is determined to be voice as represented by arrows 840, 845 and 850. However, when the current audio frame is determined to

003239.P010 -17- WWS/wlr

10

15

be silence, the operating mode of the system depends on the current state of state machine 800. For example, if state machine 800 is in SILENCE SUPPRESSION state 820, state machine 800 remains in that state as represented by arrow 855. However, if state machine 800 is in VOICE state 810 and the current audio frame is determined to be silence, state machine enters into HANGOVER state 830 as represented by arrow 860. Consequently, only after a predetermined number (Q) of subsequent audio frames are determined to be silence (# of frames  $\geq$  Q), state machine 800 enters into SILENCE SUPPRESSION state 820 as represented by arrow 865. However, if prior to that time, the sampled audio frame is determined to be voice, state machine enters into VOICE state 810 as represented by arrow 850. As a result of these operations, speech clipping is substantially avoided.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other modifications may occur to those ordinarily skilled in the art.

003239.P010 -18- WWS/wlr

## **CLAIMS**

## What is claimed is:

1	1. A method for enhancing voice activity detection comprising:
2	determining a peak-to-mean likelihood ratio; and
3	comparing the peak-to-mean likelihood ratio to a selected threshold to
4	determine whether a current audio frame represents a voice signal.
1	2. The method of claim 1, wherein prior to determining the peak-
2	to-mean likelihood ratio, the method further comprises:
3	determining a short-term averaged energy for the current audio frame;
4	and
5	determining a long-term averaged energy for the current audio frame.
1	3. The method of claim 2, wherein after determining the short-
2	term averaged energy and the long-term averaged energy, the method further
3	comprises:
4	determining whether a sum of the short-term averaged energy and a
5	factor is greater than the long-term averaged energy; and
6	determining that the current audio frame represents silence if the sum
7	is less than the long-term averaged energy, without necessitating a
8	determination of the peak-to-mean likelihood ratio.

1	4. The method of claim 3, upon determining that the sum is
2	greater than the long-term averaged energy and before determining the peak-
3	to-mean likelihood ratio, the method further comprises:
4	determining whether a difference between the long-term averaged
5	energy and the short-term averaged energy is less than a predetermined
6	threshold;
7	determining that the current audio frame represents voice if the
8	difference is greater than the predetermined threshold; and
9	continuing by determining the peak-to-mean likelihood ratio if the
10	difference is less than the predetermined threshold.
1	5. The method of claim 2, wherein the determining of the short-
2	term averaged energy comprises:
3	determining an energy, in decibels, of the current audio frame;
4	determining a short-term averaged energy for a prior audio frame; and
5	conducting a weighted average of the energy of the current audio frame

6. The method of claim 1, wherein the determining a peak-tomean likelihood ratio comprises

calculating an averaged peak-to-mean ratio for the current audio
frame;

and the short-term averaged energy for the prior audio frame.

- 5 determining a maximum averaged peak-to-mean ratio;
- 6 determining a minimum averaged peak-to-mean ratio;

003239.P010 -20- WWS/wlr

7	determining a first result being a difference between the maximum
8	averaged peak-to-mean ratio and the averaged peak-to-mean ratio for the
9	current audio frame;
10	determining a second result being a difference between the maximum

averaged peak-to-mean ratio and the minimum averaged peak-to-mean ratio; and

13 conducting a ratio between the first result and the second result to 14 produce the peak-to-mean likelihood ratio.

- 7. A communication module comprising:
- 2 a substrate;

1

1

2

- a processing unit placed on the substrate; and
- a memory coupled to the processing unit, the memory to contain a voice activity detector which, when executed by the processing unit, analyzes
- 6 a short-term averaged energy, a long-term averaged energy, and a peak-to-
- 7 mean likelihood ratio in order to determine whether a current audio frame
- 8 represents voice or silence.
- 8. The communication module of claim 7, wherein the voice activity detector, when executed, controls the processing unit to determine whether a sum of the short-term averaged energy and a predetermined factor is greater than the long-term averaged energy, and to signal that the current audio frame represents silence if the sum is less than the long-term averaged energy.
  - 9. The communication module of claim 8, wherein the voice activity detector, when executed, controls the processing unit to determine

003239.P010 -21- WWS/wlr

- 3 whether a difference between the long-term averaged energy and the short-
- 4 term averaged energy is less than a predetermined threshold, and to signal
- 5 that the current audio frame represents voice if the difference is greater than
- 6 the predetermined threshold.
- 1 10. The communication module of claim 9, wherein the voice
- 2 activity detector, when executed, controls the processing unit to determine
- 3 the peak-to-mean likelihood ratio, and to compare the peak-to-mean
- 4 likelihood ratio to a selected threshold to determine whether a current audio
- 5 frame represents a voice signal.
- 1 11. The communication module of claim 10, wherein the voice
- 2 activity detector, when executed, controls the processing unit to determine a
- 3 peak-to-mean ratio by (i) sampling an analog signal a predetermined number
- 4 of times to produce a plurality of sampled signals each having a sampled
- 5 value, (ii) determining a maximum value of the plurality of sampled signals,
- 6 and (iii) conducting a ratio between an absolute value of the maximum value
- 7 and a summation of the sampled values for the plurality of sampled signals.
- 1 12. The communication module of claim 10, wherein the voice
- 2 activity detector, when executed, controls the processing unit to determine an
- 3 averaged peak-to-mean ratio for the current audio frame by (i) monitoring a
- 4 maximum averaged peak-to-mean ratio and a minimum averaged peak-to-
- 5 mean ratio, (ii) determining a first result being a difference between the
- 6 maximum averaged peak-to-mean ratio and the averaged peak-to-mean ratio
- 7 for the current audio frame, (iii) determining a second result being a
- 8 difference between the maximum averaged peak-to-mean ratio and the

003239.P010 -22- WWS/wlr

2

3

4

5

- 9 minimum averaged peak-to-mean ratio, and (iv) conducting a ratio between 10 the first result and the second result to produce the peak-to-mean likelihood 11 ratio.
- 1 13. A machine readable medium having embodied thereon a 2 computer program for processing by a machine, the computer program 3 comprising:
- a first routine for determining a peak-to-mean likelihood ratio; and
  a second routine for comparing the peak-to-mean likelihood ratio to a
  selected threshold to determine whether an audio frame being transmitted
  represents a voice signal.
  - 14. The machine readable medium of claim 13, wherein the computer program further comprising:
  - a third routine for determining a short-term averaged energy for the audio frame, the third routine being executed before the first and second routines; and
- a fourth routine for determining a long-term averaged energy for the audio frame, the fourth routine being executed before the first and second routines.
- 1 15. The machine readable medium of claim 14, wherein the computer program further comprising:
- a fifth routine for determining whether a sum of the short-term

  averaged energy and a predetermined factor is greater than the long-term

  averaged energy, the fifth routine being executed before the first and second

  routines; and

003239.P010 -23- WWS/wlr

2

3

1

2

3

4

5

6

7

8

9

10

11

12

- a sixth routine for determining whether a difference between the longterm averaged energy and the short-term averaged energy is less than a

  predetermined threshold, the sixth routine being executed after determining
  that the sum is greater than the long-term averaged energy and before
  execution of the first and second routines.
- 1 16. The machine readable medium of claim 15, wherein the fifth 2 routine determining that the current audio frame represents silence if the 3 sum is less than the long-term averaged energy.
  - 17. The machine readable medium of claim 15, wherein the sixth routine determining that the current audio frame represents voice if the difference is greater than the predetermined threshold.
  - 18. A voice activity detector comprising:

    circuitry to determine a short-term averaged energy for an audio frame;

    circuitry to determine a long-term averaged energy for the audio frame;

    circuitry to determine whether the short-term averaged energy is

    greater than the long-term averaged energy by a predetermined factor;

    circuitry to determine whether a difference between the long-term

    averaged energy and the short-term averaged energy is less than a

predetermined threshold when the short-term averaged energy is greater

circuitry to determine a peak-to-mean likelihood ratio when the difference between the long-term averaged energy and the short-term averaged energy is less than the predetermined threshold; and

than the long-term averaged energy by the predetermined factor;

003239.P010 -24- WWS/wlr

circuitry to comparing the peak-to-mean likelihood ratio to a selected threshold and to determine that the audio frame represents a voice signal when the peak-to-mean likelihood ratio is greater than a selected threshold.

10

#### ABSTRACT OF THE DISCLOSURE

A voice activity detector to analyze a short-term averaged energy (STAE), a long-term averaged energy (LTAE), and a peak-to-mean likelihood ratio (PMLR) in order to determine whether a current audio frame being transmitted represents voice or silence. This is accomplished by determining whether a sum of the STAE and a factor is greater than the LTAE. If not, the current audio frame represents silence. If so, a second set of determinations is performed. Herein, a determination is made as to whether the difference between the LTAE and the STAE is less than a predetermined threshold. If so, the current audio frame represents voice. Otherwise, the PMLR is determined and compared to a selected threshold. If the PMLR is greater than the selected threshold, the current audio frame represents a voice signal. Otherwise, it represents silence.

003239.P010 -26- WWS/wlr




Figure 1




Figure 2






Figure 3








Figure 8




Figure 9




Figure 10

MICOM SIMI→

Attorbey's Docket No.: 003239 F010

## DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or any original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

#### A VOICE ACTIVITY DETECTOR FOR PACKET VOICE NETWORK

the sy	pecification of which	is attached hereto. was filed on United States Application Number or PCT International Application Number and was amended on	
			(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

APPLICATION NUMBER	COUNTRY (OR INDICATE IS PCT)	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 37 USC 119
			□No □Yes
			□ No □ Yes
			□No □Yes

I hereby claim the benefit under Tirle 35, United States Code, Section 119(e) of any United States provisional application(s) listed below:

APPLICATION NUMBER	FILING DATE	

Docket No. 603239.P010

Pg 1

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

AFPLICATION NUMBER	FILING DATE	STATUS (ISSUED, PENDING, ABANDONED)

I hereby appoint BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, a firm including: Farzaid E. Amini, Reg. No. P42,261; Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbit, Reg. No. 39,591; Carol F. Barry, P41,600; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Bereznak, Reg. No. 33,474; Michael A. Bernadicou, Reg. No. 35,934; Roger W. Blakely, J., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Kent M. Chen, Reg. No. 39,630; Lawrence M. Cho, Reg. No. 39,942; Yong S. Choi, Reg. No. No. P43,374; Thomas M. Coester, Reg. No. 39,630; Lawrence M. Cho, Reg. No. 39,942; Yong S. Choi, Reg. No. No. P43,374; Thomas M. Coester, Reg. No. 39,637; Roland B. Cortes, Reg. No. 39,152; Barbera Bokanov Courinsy, Reg. No. P42,442; William Donald Davis, Reg. No. 38,428; Michael Anthony DeSanotis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Tarek N. Fahmi, Reg. No. P41,402; James Y. Go, Reg. No. 40,621; Richard Leon Gregory, Jr., P42,607; Dinu Gruia, Reg. No. P41,402; James Y. Go, Reg. No. 40,621; Richard Leon Gregory, Jr., P42,607; Dinu Gruia, Reg. No. P41,839; Willimore F. Holbrow III, Reg. No. P41,845; George W. Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; Dag H. Johansen, Reg. No. 36,172; William W. Kidd. Reg. No. 31,772; Tim L. Kitcher, Reg. No. 91,900; Michael J. Milliè, Reg. No. 36,172; William W. Kidd. Reg. No. 31,772; Tim L. Kitcher, Reg. No. 19,190; Michael No. P42,096; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 40,171; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Allan T. Sponseller, Reg. No. 39,384; Geofftey T. Staniford, P3,151; Judith A. Szepesi, Reg. No. 39,393; Vincent P. Tassinari, Reg. No. 94,2479; Edwiny H. Taylor, Reg. No. 25,129; George G. C. Tsong, Reg. No. 41,355; Lester J. Vincent, Reg. No. 31,460; John Patrick Ward, Reg. No. 40,216; Stephen Warfola, P43,237; Ben J. Yorks, Reg. No. 33,609; and Norman Zafman, Reg. No. 26,250; my attorneys; and Amy M. Armstrong, Reg. No. P42,267; Robert Andrew Diehl, Reg. No. 84,092; and E

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor (given name, family name)	Zifei Peter Wang
Inventor's Signature Some Pater Ward	Date 8/14/98
Residence Thousand Oaks, California (City, State)	Citizenship Peoples Republic of China (Country)
P. O. Address 535 N. Oak Tree Lane, #B	
Thousand Oaks, California 91360 USA	

Docket No. 003239.P010

Pg 2